OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CONDUIT ADAPTORS AND ACCESSORIES

Progress® Adaptor, Progress® Kombi EMC

1165.80.32.250
Adapter EMC NPB, M32, long, ø21…25mm



- Adapters with integrated glands
- EMC versions
- Rail Approved EN 45545 option
- Thrust collars

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M32
Inner thread size	M32
Insert Type	One-Piece
Cable diameter min	21 mm
Cable diameter max	25 mm
IP class	Cable gland IP 68

DIMENSIONS

Thread pitch	1.5
Inner thread pitch	1.5 mm
Thread length	13 mm
Height (H)	49 mm
Spanner width (AF)	36 mm

MATERIALS

Material	Nickel-plated brass
Materials O-ring	NBR

Material of seals	TPE
Contact sleeve material	Nickel-plated brass
Temperature range	-40°C ... +100°C

APPROVALS

Approvals	SEV, CE, DNV, EAC, VDE
Strain relief	Version A acc. to EN 62444

ADDITIONAL DATA

Pack size	10
Country of origin	CH
Tariff code	74199949
Weight	157.3 g
Additional features	Max. clamping range depends on conduit inner diameter

