OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# CONDUIT ADAPTORS AND ACCESSORIES

Progress® Adaptor, Progress® Kombi EMC

1165.80.50.410
Adapter EMC NPB, M50, long, ø37…41mm



- Adapters with integrated glands
- EMC versions
- Rail Approved EN 45545 option
- Thrust collars

**PRODUCT DESCRIPTION**

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Thread Size (G)** | M50 |
| **Inner thread size** | M50 |
| **Insert Type** | One-Piece |
| **Cable diameter min** | 37 mm |
| **Cable diameter max** | 41 mm |
| **IP class** | Cable gland IP 68 |

## DIMENSIONS

| | |
|---|---|
| **Thread pitch** | 1.5 |
| **Inner thread pitch** | 1.5 mm |
| **Thread length** | 14 mm |
| **Height (H)** | 55 mm |
| **Spanner width (AF)** | 55 mm |

## MATERIALS

| | |
|---|---|
| **Material** | Nickel-plated brass |
| **Materials O-ring** | NBR |

| | |
|---|---|
| **Material of seals** | TPE |
| **Contact sleeve material** | Nickel-plated brass |
| **Temperature range** | -40°C ... +100°C |

## APPROVALS

| | |
|---|---|
| **Approvals** | SEV, CE, DNV, EAC, VDE |
| **Strain relief** | Version A acc. to EN 62444 |

## ADDITIONAL DATA

| | |
|---|---|
| **Pack size** | 5 |
| **Country of origin** | CH |
| **Tariff code** | 74199949 |
| **Weight** | 351.7 g |
| **Additional features** | Max. clamping range depends on conduit inner diameter |

