


CONDUIT ADAPTORS AND ACCESSORIES

Progress® Adaptor, Progress® Kombi EMC

1165.80.50.370
Adapter EMC NPB, M50, long, ø33...37mm

- Adapters with integrated glands
- EMC versions
- Rail Approved EN 45545 option
- Thrust collars



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M50
Inner thread size	M50
Insert Type	One-Piece
Cable diameter min	33 mm
Cable diameter max	37 mm
IP class	Cable gland IP 68

DIMENSIONS

Thread pitch	1.5
Inner thread pitch	1.5 mm
Thread length	14 mm
Height (H)	55 mm
Spanner width (AF)	55 mm

MATERIALS

Material	Nickel-plated brass
----------	---------------------

Materials O-ring	NBR
Material of seals	TPE
Contact sleeve material	Nickel-plated brass
Temperature range	-40°C ... +100°C

APPROVALS

Approvals	SEV, CE, DNV, EAC, VDE
Strain relief	Version A acc. to EN 62444

ADDITIONAL DATA

Pack size	5
Country of origin	CH
Tariff code	74199949
Weight	355.3 g
Additional features	Max. clamping range depends on conduit inner diameter