OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CONDUIT ADAPTORS AND ACCESSORIES

Progress® Adaptor, Progress® Kombi EMC

1165.80.48.465
Adapter EMC NPB, Pg 48, long, ø43…46.5mm



- Adapters with integrated glands
- EMC versions
- Rail Approved EN 45545 option
- Thrust collars

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	PG 48
Inner thread size	PG 48
Insert Type	One-Piece
Cable diameter min	43 mm
Cable diameter max	46.5 mm
IP class	Cable gland IP 68

DIMENSIONS

Thread length	15 mm
Height (H)	59 mm
Spanner width (AF)	65 mm

MATERIALS

Material	Nickel-plated brass
Materials O-ring	NBR
Material of seals	TPE
Contact sleeve material	Nickel-plated brass

Temperature range	-40°C ... +100°C

APPROVALS

Approvals	EAC

ADDITIONAL DATA

Pack size	5
Country of origin	CH
Tariff code	74199949
Weight	570.8 g
Additional features	Max. clamping range depends on conduit inner diameter

