OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CONDUIT ADAPTORS AND ACCESSORIES

Progress® Adaptor, Progress® Kombi EMC

1165.80.12.075
Adapter EMC NPB, M12, long, ø6…7.5mm



- Adapters with integrated glands
- EMC versions
- Rail Approved EN 45545 option
- Thrust collars

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M12
Inner thread size	M12
Insert Type	One-Piece
Cable diameter min	6 mm
Cable diameter max	7.5 mm
IP class	Cable gland IP 68

DIMENSIONS

Thread pitch	1.5
Inner thread pitch	1.5 mm
Thread length	10 mm
Height (H)	34 mm
Spanner width (AF)	15 mm

MATERIALS

Material	Nickel-plated brass
Materials O-ring	NBR

Material of seals	TPE
Contact sleeve material	Nickel-plated brass
Temperature range	-40°C ... +100°C

APPROVALS

Approvals	SEV, CE, DNV, EAC, VDE
Strain relief	Version A acc. to EN 62444

ADDITIONAL DATA

Pack size	50
Country of origin	CH
Tariff code	74199949
Weight	27.44 g
Additional features	Max. clamping range depends on conduit inner diameter

