OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

EMC HIGH TEMPERATURE - CONTACT SLEEVE

Progress® MS EMC HT

1180.10.91.060
Gland EMC NPB, sleeve, High temp, M10, long, ø4… 6mm



- Permenant contact pressure
- 360° contact sleeve construction
- -40°C…+200°C
- IP68 up to 10 bar, IP69K

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M10
Insert Type	One-Piece
Cable diameter min	4 mm
Cable diameter max	6 mm
IP class	IP 68 (up to 10 bar), IP 69 further protection

DIMENSIONS

Thread pitch	1.5
Thread length	10 mm
Height (H)	16 mm
Spanner width (AF)	13 mm

MATERIALS

Material	Nickel-plated brass
Materials O-ring	FPM
Material of seals	FPM
Contact sleeve material	Nickel-plated brass

Temperature range	-40°C ... +200°C

APPROVALS

Approvals	EAC
Strain relief	Version A acc. to EN 62444

ADDITIONAL DATA

Pack size	50
Country of origin	CH
Tariff code	74199949
Weight	12.06 g
Additional features	Metric coarse-pitch thread

