OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

EMC - CONTACT SLEEVE

Progress® MS EMC

1180.32.210
Gland EMC NPB, sleeve, M32, long, ø18…21mm



- Permenant contact pressure
- 360° contact sleeve construction
- -40°C…+100°C
- IP68 up to 10 bar, IP69K

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M32
Insert Type	One-Piece
Cable diameter min	18 mm
Cable diameter max	21 mm
IP class	IP 68 (up to 10 bar), IP 69 further protection

DIMENSIONS

Thread pitch	1.5
Thread length	13 mm
Height (H)	32 mm
Spanner width (AF)	36 mm

MATERIALS

Material	Nickel-plated brass
Materials O-ring	NBR
Material of seals	TPE
Contact sleeve material	Nickel-plated brass

Temperature range	-40°C ... +100°C

APPROVALS

Approvals	SEV, CE, cRUus, DNV, EAC, VDE
Strain relief	Version A acc. to EN 62444

ADDITIONAL DATA

Pack size	25
Country of origin	CH
Tariff code	74199949
Weight	114.64 g

