

#### **OEM Automatic Ltd**

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **COMBINATION CONDUIT GLANDS**

Progress® Kombi

• Conduit glands


• -40°C...+100°C

• IP68

1710.60.36.45 Combi Conduit Gland NPB, Pg 36, long - ø45mm, ø26...35mm

• Rail approved versions to EN 45545





#### PRODUCT DESCRIPTION

AGRO Combination conduit glands are an ideal solution if you want to introduce cables inside a conduit into an enclosure and at the same time want a secure, seal and add strain relief for the cables inside.

The integrated cable gland achieves excellent sealing (IP 68) inside the conduit. This ensure the enclosure stay free from water and condensation ingress.

Integrated EMC cable gland

The combination conduit gland is also available in a special version for shielded cables.

For railway applications where cables are laid in conduits in order to protect them from impacts or manipulation – the same requirements apply as for cable glands: the combination conduit glands must be equipped with a sealing insert made of special TPE according to the requirements of EN 45545.

These are available on request and the part number is just prefixed by a capital 'F'.

### **TECHNICAL DATA**

#### **GENERAL DATA**

Thread Size (G)	PG 36
Insert Type	Two-Piece
Cable diameter inner min	26 mm
Cable diameter inner max	30.5 mm
Cable diameter min	30.5 mm
Cable diameter max	35 mm
IP class	Cable gland IP 68

#### **DIMENSIONS**

Thread length	15 mm
Height (H)	60 mm
Spanner width (AF)	54 mm
Conduit diameter (AD)	45 mm

## **MATERIALS**

Material	Nickel-plated brass
Materials O-ring	NBR
Material of seals	TPE
Temperature range	-40°C +100°C

# **APPROVALS**

# **ADDITIONAL DATA**

Pack size	10
Country of origin	СН
Tariff code	74199949
Weight	421.4 g
Additional features	Max. clamping range depends on conduit inner diameter

