


## COMBINATION CONDUIT GLANDS

Progress® Kombi

1710.60.25.3/4

Combi Conduit Gland NPB, M25, long -  $\varnothing 3/4"$ ,  $\varnothing 12.5 \dots 20.5 \text{ mm}$

- Conduit glands
- Rail approved versions to EN 45545
- $-40^{\circ}\text{C} \dots +100^{\circ}\text{C}$
- IP68



### PRODUCT DESCRIPTION

AGRO Combination conduit glands are an ideal solution if you want to introduce cables inside a conduit into an enclosure and at the same time want a secure, seal and add strain relief for the cables inside.

The integrated cable gland achieves excellent sealing (IP 68) inside the conduit. This ensure the enclosure stay free from water and condensation ingress.

Integrated EMC cable gland

The combination conduit gland is also available in a special version for shielded cables.

For railway applications where cables are laid in conduits in order to protect them from impacts or manipulation – the same requirements apply as for cable glands: the combination conduit glands must be equipped with a sealing insert made of special TPE according to the requirements of EN 45545.

These are available on request and the part number is just prefixed by a capital 'F'.

## TECHNICAL DATA

### GENERAL DATA

Thread Size (G)	M25
Insert Type	Two-Piece
Cable diameter inner min	12.5 mm
Cable diameter inner max	16 mm
Cable diameter min	16 mm
Cable diameter max	19 mm
IP class	Cable gland IP 68

### DIMENSIONS

Thread pitch	1.5
Thread length	11 mm
Height (H)	52 mm
Spanner width (AF)	36 mm
Conduit diameter (AD)	3/4"

**MATERIALS**

Material	Nickel-plated brass
Materials O-ring	NBR
Material of seals	TPE
Temperature range	-40°C ... +100°C

**APPROVALS**

Approvals	SEV, CE, DNV, EAC, VDE
Strain relief	Version A acc. to EN 62444

**ADDITIONAL DATA**

Pack size	25
Country of origin	CH
Tariff code	74199949
Weight	174.32 g
Additional features	Max. clamping range depends on conduit inner diameter

