


OEM Automatic Ltd Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

90° ELBOW GLANDS AND 45°/90° ELBOWS

Progress® Elbow

5210.09 Gland NPB, 90° elbow, Pg 9, long, ø6...10.5mm

- Nickel plated brass
- Ideal for tight spaces
- thread adaptor versions
- -40°C...+100°C
- up to IP68



PRODUCT DESCRIPTION

The popular Progress® range of nickel-plated brass are also available with 90° elbow, so ideal for tight spaces.

In addition to the glands, there are also a range of 90° and 45° elbows with internal & external threads to give additional flexibility.

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	PG 9
Insert Type	Two-Piece
Cable diameter inner min	6 mm
Cable diameter inner max	8 mm
Cable diameter min	8 mm
Cable diameter max	10.5 mm
IP class	IP 68
DIMENSIONS	

Thread length	11 mm
Height (H)	34 mm
Spanner width (AF)	18 mm
Width (B)	36 mm



Centres (A)	13 mm
MATERIALS	
Material	Nickel-plated brass
Material of seals	TPE
Temperature range	-40°C +100°C
APPROVALS	
Approvals	EAC
Entry thread IP class	IP 68, if entry thread is sealed
ADDITIONAL DATA	
Pack size	50
Country of origin	СН
Tariff code	74199949
Weight	33 g

