


## 90° ELBOW GLANDS AND 45°/90° ELBOWS

### Progress® Elbow

5210.20

Gland NPB, 90° elbow, M20, long, ø8...15mm

- Nickel plated brass
- Ideal for tight spaces
- thread adaptor versions
- -40°C...+100°C
- up to IP68



### PRODUCT DESCRIPTION

The popular Progress® range of nickel-plated brass are also available with 90° elbow, so ideal for tight spaces.

In addition to the glands, there are also a range of 90° and 45° elbows with internal & external threads to give additional flexibility.

## TECHNICAL DATA

### GENERAL DATA

Thread Size (G)	M20
Insert Type	Two-Piece
Cable diameter inner min	8 mm
Cable diameter inner max	11 mm
Cable diameter min	11 mm
Cable diameter max	15 mm
IP class	IP 68

### DIMENSIONS

Thread pitch	1.5
Thread length	12 mm
Height (H)	39 mm
Spanner width (AF)	24 mm

Width (B)	44 mm
Centres (A)	16 mm

### MATERIALS

Material	Nickel-plated brass
Material of seals	TPE
Temperature range	-40°C ... +100°C

### APPROVALS

Approvals	SEV, CE, DNV, EAC, VDE
Strain relief	Version A acc. to EN 62444
Entry thread IP class	IP 68, if entry thread is sealed

### ADDITIONAL DATA

Pack size	50
Country of origin	CH
Tariff code	74199949
Weight	62.5 g

