**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# 90° ELBOW GLANDS AND 45°/90° ELBOWS

Progress® Elbow

5200.16
Gland NPB, 90° elbow, Pg 16, ø8…15mm



- Nickel plated brass
- Ideal for tight spaces
- thread adaptor versions
- -40°C…+100°C
- up to IP68

### PRODUCT DESCRIPTION

The popular Progress® range of nickel-plated brass are also available with 90° elbow, so ideal for tight spaces.

In addition to the glands, there are also a range of 90° and 45° elbows with internal & external threads to give additional flexibility.

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Thread Size (G)** | PG 16 |
| **Insert Type** | Two-Piece |
| **Cable diameter inner min** | 8 mm |
| **Cable diameter inner max** | 11 mm |
| **Cable diameter min** | 11 mm |
| **Cable diameter max** | 15 mm |
| **IP class** | IP 68 |

## DIMENSIONS

| | |
|---|---|
| **Thread length** | 10 mm |
| **Height (H)** | 41 mm |
| **Spanner width (AF)** | 24 mm |
| **Width (B)** | 44 mm |
| **Centres (A)** | 16 mm |

## MATERIALS

| | |
|---|---|
| **Material** | Nickel-plated brass |
| **Material of seals** | TPE |
| **Temperature range** | -40°C ... +100°C |

## APPROVALS

| | |
|---|---|
| **Approvals** | EAC |
| **Entry thread IP class** | IP 68, if entry thread is sealed |

## ADDITIONAL DATA

| | |
|---|---|
| **Pack size** | 50 |
| **Country of origin** | CH |
| **Tariff code** | 74199949 |
| **Weight** | 63.06 g |

