

#### **OEM Automatic Ltd**

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk


# 90° ELBOW GLANDS AND 45°/90° ELBOWS

Progress® Elbow

5210.17 Gland NPB, 90° elbow, M16, long, ø6...10.5mm

- Nickel plated brass
- Ideal for tight spaces
- thread adaptor versions
- -40°C...+100°C
- up to IP68





#### PRODUCT DESCRIPTION

The popular Progress® range of nickel-plated brass are also available with 90° elbow, so ideal for tight spaces.

In addition to the glands, there are also a range of 90° and 45° elbows with internal & external threads to give additional flexibility.

#### **TECHNICAL DATA**

#### **GENERAL DATA**

Thread Size (G)	M16
Insert Type	Two-Piece
Cable diameter inner min	6 mm
Cable diameter inner max	8 mm
Cable diameter min	8 mm
Cable diameter max	10.5 mm
IP class	IP 68

#### **DIMENSIONS**

Thread pitch	1.5
Thread length	12 mm
Height (H)	34 mm
Spanner width (AF)	18 mm

Width (B)	36 mm
Centres (A)	13 mm

### **MATERIALS**

Material	Nickel-plated brass
Material of seals	TPE
Temperature range	-40°C +100°C

# **APPROVALS**

Approvals	SEV, CE, DNV, EAC, VDE
Strain relief	Version A acc. to EN 62444
Entry thread IP class	IP 68, if entry thread is sealed

## **ADDITIONAL DATA**

Pack size	50
Country of origin	СН
Tariff code	74199949
Weight	35.6 g

