


OEM Automatic Ltd Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

90° ELBOW GLANDS AND 45°/90° ELBOWS



5612 90° elbow NPB, with internal & external thread

- Nickel plated brass
- Ideal for tight spaces
- thread adaptor versions
- -40°C...+100°C
- up to IP68



PRODUCT DESCRIPTION

The popular Progress® range of nickel-plated brass are also available with 90° elbow, so ideal for tight spaces.

In addition to the glands, there are also a range of 90° and 45° elbows with internal & external threads to give additional flexibility.

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M12
Inner thread size	M12
IP class	IP 54, IP 68 further protection if entry thread is sealed
DIMENSIONS	
Thread pitch	1.5
Inner thread pitch	1.5 mm
Thread length	5 mm
Height (H)	20 mm
Overall diameter (D)	15 mm
Width (B)	25 mm
Centres (A)	13 mm
Inner thread length (L1)	7 mm



MATERIALS

Material	Nickel-plated brass
Materials O-ring	NBR
Temperature range	-40°C+100°C
ADDITIONAL DATA	
Pack size	50
Country of origin	СН
Tariff code	74199949
Weight	20.7 g