**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# EX GLAND ACCESSORIES

8841.16
Locking screw synthetic, Ex e II, Pg 16




- Locking Plugs
- Pressure balancing elements
- Adapters

**PRODUCT DESCRIPTION**

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Thread Size (G)** | PG 16 |
| **IP class** | IP 68 |

## DIMENSIONS

| | |
|---|---|
| **Thread length** | 10.5 mm |
| **Height (H)** | 16 mm |
| **Spanner width (AF)** | 28 mm |
| **Allen key size** | 8 mm |

## MATERIALS

| | |
|---|---|
| **Material** | Polyamide |
| **Materials O-ring** | NBR |
| **Temperature range** | -20°C ... +90°C |

## APPROVALS

| | |
|---|---|
| **Approvals** | CE, EX, IECEx |
| **Test standard** | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| **Ex zones** | Gas 1 and 2 / dust 21 and 22 |
| **Ex-Zone gas** | II 2G Ex eb IIC Gb |
| **EX-zone dust** | II 2D Ex tb IIIC Db |
| **IECEx certificate** | IECEx BVS 07.0021 |
| **Certificate** | DMT 03 ATEX E 049 |

## ADDITIONAL DATA

| | |
|---|---|
| **Pack size** | 100 |

