


FLAMEPROOF COMPACT NICKEL PLATED

Flameproof Compact

EX1126.50.420

Gland Ex Compact NPB, Ex d IIC, Ex e II, M50, ø35...
42mm

- Ex d IIC/ Ex e II
- -60°C...+105°C
- Clamped versions
- IECEx approved
- IP68 up to 30 bar



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M50
Insert Type	One-Piece
Cable diameter min	35 mm
Cable diameter max	42 mm
IP class	IP 68 (30 bar)

DIMENSIONS

Thread pitch	1.5
Thread length	14 mm
Height (H)	35 mm
Spanner width (AF)	60 mm

MATERIALS

Material	Nickel-plated brass
Materials O-ring	FPM
Material of seals	NBR

Temperature range	-60°C ... +105°C
-------------------	------------------

APPROVALS

Approvals	CE, DNV, EX, IECEx
Test standard	IEC EN 60079-0 / IEC EN 60079-1 / IEC EN 60079-7 / IEC EN 60079-31
Ex zones	Gas 1 and 2 / dust 21 and 22
Ex-Zone gas	II 2G Ex db eb IIC
EX-zone dust	II 2D Ex ta IIC
IECEX certificate	IECEX PTB 12.0055X
Certificate	PTB 10 ATEX 1034X

ADDITIONAL DATA

Pack size	5
Country of origin	CH
Tariff code	74199949
Weight	366.8 g

