OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SYNTHETIC GFK EX - EX E II, EX I II

Progress GFK Ex

EX1530.48.490
Gland Ex synthetic, Ex e II, Ex i II, blue, Pg 48, ø47…49mm



- Ex e II, Ex i II
- Intrinsicly Safe - Blue
- -20°C…+85°C
- IECEx approved
- IP66/IP68 up to 10 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	PG 48
Insert Type	One-Piece
Cable diameter min	47 mm
Cable diameter max	49 mm
IP class	IP 68
Colour	Black / light blue

DIMENSIONS

Thread length	16 mm
Height (H)	46 mm
Spanner width (AF)	70 mm

MATERIALS

Material	Fiberglass reinforced polyamide
Material of seals	NBR, TPE
Temperature range	-20°C ... +85°C

APPROVALS

Approvals	CE, DNV, EX, IECEx
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Ex zones	Gas 0, 1 and 2 / dust 20, 21 and 22
Ex-Zone gas	II 2G Ex eb IIC Gb
EX-zone dust	II 2D Ex tb IIIC Db
Intrinsic safety gas	II 2G Ex ia IIC Ga
Intrinsic safety dust	II 2D Ex ia IIIC Da
IECEx certificate	IECEx SEV 15.0019X
Certificate	SEV 15 ATEX 0152X

ADDITIONAL DATA

Pack size	5
Country of origin	CH
Tariff code	39269000
Weight	150 g