


SYNTHETIC GFK EX - EX E II, EX I II

Progress GFK Ex

EX1530.09.080

Gland Ex synthetic, Ex e II, Ex i II, blue, Pg 9, ø6...8mm

- Ex e II, Ex i II
- Intrinsically Safe - Blue
- -20°C...+85°C
- IECEx approved
- IP66/IP68 up to 10 bar

**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Thread Size (G)	PG 9
Insert Type	One-Piece
Cable diameter min	6 mm
Cable diameter max	8 mm
IP class	IP 68
Colour	Black / light blue

DIMENSIONS

Thread length	12 mm
Height (H)	26 mm
Spanner width (AF)	21 mm

MATERIALS

Material	Fiberglass reinforced polyamide
Material of seals	NBR, TPE
Temperature range	-20°C ... +85°C

APPROVALS

Approvals	CE, DNV, EX, IECEx
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Ex zones	Gas 0, 1 and 2 / dust 20, 21 and 22
Ex-Zone gas	II 2G Ex eb IIC Gb
EX-zone dust	II 2D Ex tb IIIC Db
Intrinsic safety gas	II 2G Ex ia IIC Ga
Intrinsic safety dust	II 2D Ex ia IIIC Da
IECEx certificate	IECEx SEV 15.0019X
Certificate	SEV 15 ATEX 0152X

ADDITIONAL DATA

Pack size	50
Country of origin	CH
Tariff code	39269000
Weight	10.9 g