


SYNTHETIC GFK EX E II

Progress® GFK Ex

EX1540.11.3.030

Gland Ex synthetic, Ex e II, black, multi, Pg 11, 3 x
ø2.5...3mm

- Ex e II
- -20°C...+85°C
- IECEx approved
- IP66/IP68 up to 10 bar



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	PG 11
Insert Type	One-Piece
Cable diameter min	2 mm
Cable diameter max	3 mm
Number of cables	3
IP class	IP 66 / IP 68
Colour	Black RAL 9005

DIMENSIONS

Thread length	12 mm
Height (H)	28 mm
Spanner width (AF)	24 mm

MATERIALS

Material	Fiberglass reinforced polyamide
Material of seals	NBR

Temperature range	-20°C ... +85°C
-------------------	-----------------

APPROVALS

Approvals	CE, DNV, EX, IECEx
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Ex zones	Gas 1 and 2 / dust 21 and 22
Ex-Zone gas	II 2G Ex eb IIC Gb
EX-zone dust	II 2D Ex tb IIIC Db
IECEX certificate	IECEX SEV 15.0019X
Certificate	SEV 15 ATEX 0152X

ADDITIONAL DATA

Pack size	50
Country of origin	CH
Tariff code	39269000
Weight	14.88 g