OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SYNTHETIC GFK EX E II

Progress® GFK Ex

EX1540.48.490
Gland Ex synthetic, Ex e II, black, Pg 48, ø47…49mm



- Ex e II
- -20°C…+85°C
- IECEx approved
- IP66/IP68 up to 10 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	PG 48
Insert Type	One-Piece
Cable diameter min	47 mm
Cable diameter max	49 mm
IP class	IP 66 / IP 68
Colour	Black RAL 9005

DIMENSIONS

Thread length	16 mm
Height (H)	46 mm
Spanner width (AF)	70 mm

MATERIALS

Material	Fiberglass reinforced polyamide
Material of seals	NBR, TPE
Temperature range	-20°C ... +85°C

APPROVALS

Approvals	CE, DNV, EX, IECEx
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Ex zones	Gas 1 and 2 / dust 21 and 22
Ex-Zone gas	II 2G Ex eb IIC Gb
EX-zone dust	II 2D Ex tb IIIC Db
IECEx certificate	IECEx SEV 15.0019X
Certificate	SEV 15 ATEX 0152X

ADDITIONAL DATA

Pack size	5
Country of origin	CH
Tariff code	39269000
Weight	170.4 g