

SYNTHETIC GFK EX E II

Progress® GFK Ex

EX1571.48.3.180

Gland Ex synthetic, Ex e II, multi, Pg 48, 3 x ø17...
18mm

- Ex e II
- -20°C...+85°C
- IECEx approved
- IP66/IP68 up to 10 bar



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	PG 48
Insert Type	One-Piece
Cable diameter min	17 mm
Cable diameter max	18 mm
Number of cables	3
IP class	IP 66 / IP 68
Colour	Grey RAL 7035

DIMENSIONS

Thread length	16 mm
Height (H)	46 mm
Spanner width (AF)	70 mm

MATERIALS

Material	Fiberglass reinforced polyamide
Material of seals	NBR

Temperature range	-20°C ... +85°C
-------------------	-----------------

APPROVALS

Approvals	CE, DNV, EX, IECEx
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Ex zones	Gas 1 and 2 / dust 21 and 22
Ex-Zone gas	II 2G Ex eb IIC Gb
EX-zone dust	II 2D Ex tb IIIC Db
IECEX certificate	IECEX SEV 15.0019X
Certificate	SEV 15 ATEX 0152X

ADDITIONAL DATA

Pack size	5
Country of origin	CH
Tariff code	39269000
Weight	175 g