

EMC EASYCONNECT EX E II

Progress® MS EMC easyCONNECT Ex e ii

EX1813.83.40

Ex EMC easyCONNECT NPB, clamped, M40



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M40
Insert Type	One-Piece
Cable diameter inner min	24 mm
Cable diameter inner max	28.5 mm
Cable diameter min	28.5 mm
Cable diameter max	33 mm
IP class	IP 66 / IP 68

DIMENSIONS

Thread pitch	1.5
Thread length	13 mm
Height (H)	51 mm
Spanner width (AF)	46 mm

MATERIALS

Material	Nickel-plated brass
Materials O-ring	FPM
Material screw	Stainless steel A2
Material insert	TPE

Temperature range	-60°C ... +100°C
-------------------	------------------

APPROVALS

Approvals	CE, EX, IECEX
-----------	---------------

Test standard	IEC 60079-0 / IEC 60079-7 / IEC 60079-31
---------------	--

Ex zones	Gas 1 and 2 / dust 21 and 22
----------	------------------------------

Ex-Zone gas	II 2G Ex eb IIC Gb
-------------	--------------------

EX-zone dust	II 2D Ex tb IIIC Db
--------------	---------------------

IECEX certificate	IECEX SEV 15.0018
-------------------	-------------------

Certificate	SEV 15 ATEX 0151
-------------	------------------

ADDITIONAL DATA

Pack size	10
-----------	----

Country of origin	CH
-------------------	----

Tariff code	74199949
-------------	----------

Weight	266.8 g
--------	---------