OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

EMC EASYCONNECT EX E II

Progress® MS EMC easyCONNECT Ex e ii

EX1803.83.63
Gland Ex EMC easyCONNECT NPB, Ex e II, clamped, M63, ø40…52mm



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M63
Insert Type	One-Piece
Cable diameter inner min	40 mm
Cable diameter inner max	46 mm
Cable diameter min	46 mm
Cable diameter max	52 mm
IP class	IP 66 / IP 68

DIMENSIONS

Thread pitch	1.5
Thread length	10 mm
Height (H)	60 mm
Spanner width (AF)	70 mm

MATERIALS

Material	Nickel-plated brass
Materials O-ring	FPM
Material screw	Stainless steel A2
Material insert	TPE
Temperature range	-60°C ... +100°C

APPROVALS

Approvals	CE, EX, IECEx
Test standard	IEC 60079-0 / IEC 60079-7 / IEC 60079-31
Ex zones	Gas 1 and 2 / dust 21 and 22
Ex-Zone gas	II 2G Ex eb IIC Gb
EX-zone dust	II 2D Ex tb IIIC Db
IECEx certificate	IECEx SEV 15.0018
Certificate	SEV 15 ATEX 0151

ADDITIONAL DATA

Pack size	5
Country of origin	CH
Tariff code	74199949
Weight	694.4 g