

EMC EASYCONNECT EX E II

Progress® MS EMC easyCONNECT Ex e II

EX1803.83.20

Gland Ex EMC easyCONNECT NPB, Ex e II, clamped,
M20, ø8...15mm



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M20
Insert Type	One-Piece
Cable diameter inner min	8 mm
Cable diameter inner max	11 mm
Cable diameter min	11.5 mm
Cable diameter max	15 mm
IP class	IP 66 / IP 68

DIMENSIONS

Thread pitch	1.5
Thread length	6 mm
Height (H)	35 mm
Spanner width (AF)	24 mm

MATERIALS

Material	Nickel-plated brass
Materials O-ring	FPM
Material screw	Stainless steel A2
Material insert	TPE

Temperature range	-60°C ... +100°C
-------------------	------------------

APPROVALS

Approvals	CE, EX, IECEx
-----------	---------------

Test standard	IEC 60079-0 / IEC 60079-7 / IEC 60079-31
---------------	--

Ex zones	Gas 1 and 2 / dust 21 and 22
----------	------------------------------

Ex-Zone gas	II 2G Ex eb IIC Gb
-------------	--------------------

EX-zone dust	II 2D Ex tb IIIC Db
--------------	---------------------

IECEx certificate	IECEx SEV 15.0018
-------------------	-------------------

Certificate	SEV 15 ATEX 0151
-------------	------------------

ADDITIONAL DATA

Pack size	50
-----------	----

Country of origin	CH
-------------------	----

Tariff code	74199949
-------------	----------

Weight	58.01 g
--------	---------