

EX GLAND ACCESSORIES

EX2450.17.34

Pressure balance element, membrane, Ex e II, M16

- Locking Plugs
- Pressure balancing elements
- Adapters



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

| | |
|-----------------|-----------------------|
| Thread Size (G) | M16 |
| IP class | IP 66 / IP 68 / IP 69 |

DIMENSIONS

| | |
|---------------|--------|
| Thread pitch | 1.5 |
| Thread length | 8 mm |
| Height (H) | 9.5 mm |

| | |
|--------------------|-------|
| Spanner width (AF) | 18 mm |
|--------------------|-------|

MATERIALS

| | |
|-------------------|------------------------|
| Material | Nickel-plated brass |
| Materials O-ring | FPM |
| Material membrane | Polyethersulfone (PES) |
| Temperature range | -60°C ... +100°C |

APPROVALS

| | |
|-------------------|---|
| Approvals | CE, EX, IECEx |
| Test standard | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Ex zones | Gas 1 and 2 / dust 21 and 22 |
| Ex-Zone gas | II 2G Ex eb IIC Gb |
| EX-zone dust | II 2D Ex tb IIIC Db |
| IECEx certificate | IECEx SEV 16.0010 |
| Certificate | SEV 16 ATEX 0143 |

ADDITIONAL DATA

| | |
|-------------------|----------|
| Pack size | 20 |
| Country of origin | CH |
| Tariff code | 74199949 |
| Weight | 21 g |

