

# MINIMOTOR - PCEF WORM GEARED MOTOR WITH FURTHER PLANETARY GEAR

PCEF5T2B5-30.5



- For clean environments
- IP67 as standard
- Up to 90Nm rated torque
- Minimal dirt trap points
- Epoxy coated with no external fan

## PRODUCT DESCRIPTION

White epoxy coating for increased protection against chemicals and harsh working environments. IP67 rated with no external fan.


MOTOR: Asynchronous single or three phase with 2 poles, totally enclosed. Thermal safety feature. Class H winding.

GEAR UNIT: Die-cast aluminium casing in the first reduction stage, with worm screw and steel casing in the second planetary stage, with three internal planetary gears. Wheel rim in bronze 120-160 HB hardness. Hardened steel screw with ground threads rotating on ball and roller bearings. Output shaft available in stainless steel upon request.

Lubrication with special long life oil. Sealing rings made in special rubber for high temperatures. . Rated torque 90 Nm. Version B3 or B5. B5/S left version - B5/D right version.

## TECHNICAL DATA

4967_Rated current (A)	1.56Δ/0.9Y
Input voltage ac	230Δ/400Y
IP class	IP67
Nominal speed	30.5 rpm
Nominal torque	69.3
Output power	190 W
Ratio	95:1



### B5/S

Type	A	B	C	D	E	F	G	H	I	L	M	N	P	Q	R	S	T	U	V	X	Page Weight (kg)
PCEF 4T2	127	56	40	24	55	8	27	67	32	200	115	95	140	93	25	148	17	9	3	60	8,400
PCEF 6T2	127	56	40	24	50	8	27	67	32	222	115	95	140	130	25	148	17	9	3	60	13,000

LCD model selection

Please see product description above for 2D and 3D drawings

LCD model selection

Please see product description above for 2D and 3D drawings

