

## MINIMOTOR - AM - SINGLE OR THREE PHASE MOTOR ONLY

AM100P-B14  
230V 1 ph 2600rpm 0.13Nm b14 mount

- Compact motor only
- 2 or 4 pole motor
- B3 or B14 mounting
- B3 or B14 mounting



### PRODUCT DESCRIPTION

#### ASYNCHRONOUS MOTOR

Single or three phase with 2 or 4 poles, totally enclosed with external ventilation.

Thermal safety cutout on the single phase model.


Class F winding. IP65 protection according to CEI EN 60529.  
Power from 9 to 270 W. Version B5 - B14.

On request:  
motor equipped with electromagnetic brake supplied at 230 Vac, marked by letter KA (AMKA) or at 24 Vdc, marked by letter KB (AMKB)

[Please click here for 2D and 3D drawings.](#)

### TECHNICAL DATA

Capacitor	3.15 $\mu$ F
Input voltage ac	230V
Nominal speed	2600 rpm
Nominal torque	0,13
Output power	35 W
Rated current	0.41A
Starting torque	0,14



B14

Type	D	E	F	G	L	L1	M	N	P	Q	T	U	V	X	X1	Y	Y1	W	Z	Price Standard Unit kg
AM_M2	9	20	3	10,2	157	137	58	40	73,5	95	6	M6	84	80	60	18	42	1,2	56	2,315
AM_M3	9	20	3	10,2	182	162	58	40	73,5	95	6	M6	84	80	60	18	67	1,2	56	3,030
AM_M4	9	20	3	10,2	212	192	58	40	73,5	95	6	M6	84	80	60	18	97	1,2	56	3,400

CMO model selection

 Electric motor  
15.05.2017

 Geared motor  
15.05.2017

 Worm gearmotor  
15.05.2017

 Brushless servomotors  
15.05.2017

 Clean products  
15.05.2017

 Sensors  
15.05.2017

Please see product description above for 2D and 3D drawings

CMO model selection

 Electric motor  
15.05.2017

 Geared motor  
15.05.2017

 Worm gearmotor  
15.05.2017

 Brushless servomotors  
15.05.2017

 Clean products  
15.05.2017

 Sensors  
15.05.2017

Please see product description above for 2D and 3D drawings