OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

GG CYLINDRICAL FUSE LINKS

gG cylindrical fuse link (8x32, 10x38, 14x51, 22x58)

420608
Cylindrical fuses gG 8x32 8A with indicator



- Breaking capacity between 20kA to 120kA)
- Available in 8x32, 10x38, 14x51 and 22x51
- Indicator and striker versions available

PRODUCT DESCRIPTION

gG fuses are suitable for general protection against overload or short circuit in a variety of electrical applications. The gG range from DF Electric include standard sizes such as 8x32, 10x38, 14x51 and 22x58 with rated currents between 0.5A up to 125A. Most current ratings are available with an indicator which lights up once a circuit has a blown. Striker versions are also available and can be used with fuseholders with a microswtch.

The fuse-links are manufactured from Ceramic and able to withstand large internal pressure and thermal shocks. gG fuses from DF Electric have high breaking capacities making them perfect for protecting elecrtical equipment in industrial applications.

TECHNICAL DATA

GENERAL DATA

Type	gG
4853_Size (mm)	8x32
Rated current	8 A
Voltage ac/dc max	400 V
Breaking capacity	20 kA
Frequency	42...62Hz
Indicator	Yes

ADDITIONAL DATA

Tariff code	85361010
Country of origin	ES
Weight	4.1 g
Pack size	10