

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

GG CYLINDRICAL FUSE LINKS

gG



420016 Cylindrical fuses gG 10X38 16A without indicator

- Breaking capacity between 20kA to 120kA)
- Available in 8x32, 10x38, 14x51 and 22x51
- Indicator and striker versions available

PRODUCT DESCRIPTION

gG fuses are suitable for general protection against overload or short circuit in a variety of electrical applications. The gG range from DF Electric include standard sizes such as 8x32, 10x38, 14x51 and 22x58 with rated currents between 0.5A up to 125A. Most current ratings are available with an indicator which lights up once a circuit has a blown. Striker versions are also available and can be used with fuseholders with a microswtch.

The fuse-links are manufactured from Ceramic and able to withstand large internal pressure and thermal shocks. gG fuses from DF Electric have high breaking capacities making them perfect for protecting elecrtical equipment in industrial applications.

TECHNICAL DATA

GENERAL DATA

TypegGSize10x38Rated current16 AVoltage ac/dc max400 VBreaking capacity20 kAFrequency4262HzIndicatorNo		
Size10x38Rated current16 AVoltage ac/dc max400 VBreaking capacity20 kA	No	No
Size 10x38 Rated current 16 A Voltage ac/dc max 400 V	4262Hz	4262Hz
Size 10x38 Rated current 16 A	20 kA	20 kA
Size 10x38	400 V	400 V
· · · · · · · · · · · · · · · · · · ·	16 A	16 A
i ype go	10x38	10x38
Tumo	gG	gG

ADDITIONAL DATA

Tariff code	85361010
Country of origin	ES
Weight	4.1 g

Pack size