OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# AM CYLINDRICAL FUSE LINKS

gG cylindrical fuse link ( 8x32, 10x38, 14x51, 22x58)

442032
Cylindrical fuses aM 22x58 32A without indicator



- Available in 8x32, 10x38, 14x51 and 22x58
- Most current ratings available with indicators
- Striker versions available

### PRODUCT DESCRIPTION

aM fuse links are desigend for short circuit protection in applications with high inrush currents such as motors and transformers. These fuses are designed to withstand the high inrush currents that occur when a motor is started without blowing prematurely.

Common applications include:

- Motor circuits
- HVAC systems
- Power distribution systems such as transformers and switchgear
- Rewneable energy systems

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Type** | aM |
| **4853_Size (mm)** | 22x58 |
| **Rated current** | 32 A |
| **Voltage ac/dc max** | 400 V |
| **Breaking capacity** | 20 kA |
| **Frequency** | 42...62Hz |
| **Indicator** | No |

## ADDITIONAL DATA

| | |
|---|---|
| **Tariff code** | 85361010 |
| **Country of origin** | ES |
| **Weight** | 4.1 g |
| **Pack size** | 10 |