


0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

GBAT CYLINDRICAL FUSE LINKS



- Available in 14×51 and 22×58 sizes
- Rated current between 2A to 80A
- Rated voltage of 600V DC
- Ideal for battery protection



PRODUCT DESCRIPTION

gBat Cylindrical fuse links, compliant with the IEC60269-7 Standard, are designed to safeguard battery systems. These fuse links offer comprehensive protection by quickly clearing overcurrents, overloads, and short-circuits, ensuring the safety of batteries, cables, and all associated switchgear installations.

gBat fuse links exhibit rapid operation during short-circuits and maintain reliable performance through continuous charge/discharge cycles. The design optimisation results in reduced power dissipations, enabling their versatile use across a broad spectrum of fuse bases, disconnectors, and fuse-switch disconnectors.

The gBat Cylindrical fuse links range is available in 14×51 and 22×58 sizes and include rated currents from 2A to 80A, and a rated voltage of 600V DC. These fuse links come in standard versions and striker versions and are compatible with fuse bases featuring microswitches.

TECHNICAL DATA

GENERAL DATA

Tariff code

| Туре | gBat |
|-------------------|--------|
| Size | 14x51 |
| Rated current | 6 A |
| Voltage dc max | 600 V |
| Breaking capacity | 50 kA |
| Frequency | 4262Hz |
| Indicator | No |
| ADDITIONAL DATA | |

85361010

sd.

| Country of origin | ES |
|-------------------|------|
| Weight | 18 g |
| Pack size | 10 |