

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SQB SQUARE BODY AR FUSE LINKS FOR SEMICONDUCTORS

SQB1 and SQB3

250325 Semiconductor High Speed fuses SQB1 aR, 80A, 690V, Flush end contact M8

- · Various current options available
- Multiple contact options
- Designed for high voltage levels (up to 690v)
- Wide operating temperature range





PRODUCT DESCRIPTION

The RAPIDPLUS® SQB Square-Body aR fuse links are high-speed semiconductor fuses engineered by DF Electric for protection of power electronic components. Available in a wide current range they support AC voltages up to 690 V. Designed for high fault-current interruption, they feature either M8 flush-end threaded contacts or robust blade contact options (80 mm or 110 mm) to ensure reliable connection in both panel-mounted and busbar systems. Their operating temperature span of –25 °C to +60 °C makes them suitable for demanding industrial environments. Each fuse is compact yet capable of clearing high-energy fault conditions, making them ideal whenever semiconductors like diodes, thyristors, IGBT modules, or triacs are used. These SQB fuses safeguard critical components in equipment such as motor drives, photovoltaic inverters, welding power supplies, UPS systems, and high-power rectifiers. The square-body design allows optimised integration into panel fuse holders, offering low l²t to protect sensitive semiconductor devices with minimal energy let-through. With a high breaking capacity and fast acting characteristics, they prevent cascading failures in voltage conversion systems, ensuring safe, reliable operation and ease of replacement across a broad range of current ratings.

TECHNICAL DATA

GENERAL DATA

Туре	SQB1 aR
Rated current	80 A
Voltage ac max	690 V

RATED OPERATING CONDITIONS

Operational temperature	-40°C - +80°C	

ADDITIONAL DATA

Tariff code	85361090
Country of origin	ES
Weight	410 g
Pack size	3