


EARTH TERMINALS - PSL 1.5-16MM

PSL

27001.2

PSL 1.5/2A, 1.5mm² Push-in Earth feed through

- Snap on
- 2 to 4 connections
- Pluggable cross connectors
- Push button cable release
- Test pick off point



PRODUCT DESCRIPTION

TECHNICAL DATA**GENERAL DATA**

Rated wire cross section	1.5 mm ²
Colour	Green/yellow
Mounting	Mounting rail TS 35/7.5
Rated impulse voltage	6 kV
Overtoltage category	III
Contamination degree	3

DIMENSIONS

Length	45 mm
Width	3.5 mm
Height TS 35/7.5	32 mm
Height	30.5 mm

CONNECTION DATA

Connections	2
Number of levels	1
Plug gauge acc. EN 60 947-1	A1

Cross connect channels	1
Cross section single wire from	0.14 mm ²
Cross section single wire to	1.5 mm ²
Cross section stranded wire from	0.14 mm ²
Cross section stranded wire to	1.5 mm ²
Cross section stranded with ferrule from	0.14 mm ²
Cross section stranded with ferrule to	1 mm ²
Rated wire cross section from	26 AWG
Rated wire cross section to	14 AWG
Stripping length	10 mm

MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-40 °C
Operating temperature to	120 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	BG
Weight	5.63 g
Pack size	50

Number of terminals per level	2
--------------------------------------	---

