
OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

EARTH TERMINALS - PSL 1.5-16MM

Push In Earth Terminals -PSL

27001.2
PSL 1.5/2A, 1.5mm² Push-in Earth feed through



- Snap on
- 2 to 4 connections
- Pluggable cross connectors
- Push button cable release
- Test pick off point

PRODUCT DESCRIPTION

Snap on range of Push In Earth Terminals from 1.5mm² to 16mm², in 2 , 3 and 4 connections that clamps to both sides of the TS35 DIN Rail.

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	15 mm²
Colour	Green/yellow
Mounting	Mounting rail TS 35/7.5
Rated impulse voltage	6 kV
Overvoltage category	III
Contamination degree	3

DIMENSIONS

Length	45 mm
Width	35 mm
Height TS 35/7.5	32 mm
Height	305 mm

CONNECTION DATA

Connections	2
Number of levels	1

Plug gauge acc. EN 60 947-1	A1
Cross connect channels	1
Cross section single wire from	14 mm²
Cross section single wire to	15 mm²
Cross section stranded wire from	14 mm²
Cross section stranded wire to	15 mm²
Cross section stranded with ferrule from	14 mm²
Cross section stranded with ferrule to	1 mm²
Rated wire cross section from	26 AWG
Rated wire cross section to	14 AWG
Stripping length	10 mm

MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-40 °C
Operating temperature to	120 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	BG
Weight	5.63 g
Pack size	50

Number of terminals per level	2

