

#### **OEM Automatic Ltd**

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk



# EARTH TERMINALS - SCREW ON - SL 2.5-35 MM<sup>2</sup>, SSL 50-70MM<sup>2</sup>

SL, SSL

1066.2 SL10/32, 10mm² Earth, TS32 G-rail \*\* OBSOLETE No Replacement \*\*

- · Screw to rail construction
- SL Material polyamide 6.6 UL94-V2
- Temperature resistance -40 °C...+105 °C
- SSL Material polyamide 6.6 UL94-V0
- Temperature resistance -40 °C...+120 °C



#### PRODUCT DESCRIPTION

The RK and SL range is the original traditional terminal range feed-through featuring the proven screw-connection system and screw in cross connectors.

This range is available with the 'multi-foot' construction, so will fit on TS35 and TS15 – 'Top Hat' rail or the less common TS32 – 'G-Rail', still used in some applications today.

The range also includes disconnect terminals, fused terminals, actuator, sensor, motor-connection terminals and a range of direct mount options.

For applications where space is at a premium the TS15 range is small and compact, but can still accommodate 4mm² cable sizes.

## **TECHNICAL DATA**

#### **GENERAL DATA**

Rated wire cross section	10 mm²
Colour	Green/yellow
Mounting	TS 32
Overvoltage category	III
Contamination degree	3
Approvals	UL, EAC

#### **DIMENSIONS**

Length	56 mm
Width	10 mm
Height TS 32	51.5 mm

# **CONNECTION DATA**

Connections	2
Number of levels	1
Plug gauge acc. EN 60 947-1	A5
Cross connect channels	1
Cross section single wire from	0.2 mm²
Cross section single wire to	10 mm²
Cross section stranded wire from	0.2 mm <sup>2</sup>
Cross section stranded wire to	10 mm²
Cross section stranded with ferrule from	0.2 mm <sup>2</sup>
Cross section stranded with ferrule to	10 mm²
Rated wire cross section from (AWG)	20
Rated wire cross section to (AWG)	6
Stripping length	12 mm
Screw size	M 4
Screw type	Slotted
Torque min	1.2
Torque max	2
MATERIALS	

# **MATERIALS**

Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

## **APPROVALS**

UL test standard	UL 1059
EAC test standard	TR ZU 004/2011

# **ADDITIONAL DATA**

Tariff code	85369010
Country of origin	DE
Weight	30 g
Pack size	80
Type of terminal	Screw Terminals, DIN Rail terminals

