

DOUBLE DECK TERMINALS - RKD 2.5-4MM²

RKD, RKDG

1581.4

RKD 4/35/SV Black, 4mm² Linked double deck

- Screw cross connectors
- Temperature resistance -40 °C...+105 °C
- Polyamide 6.6 UL94-V2
- Same level screw option
- Versions with electronic components fitted



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	4 mm ²
Colour	Black
Rated voltage IEC	500 V
Rated current IEC	32 A
Mounting	TS 35
Rated impulse voltage	6 kV
Overvoltage category	III
Contamination degree	3
Approvals	CSA, CSA US, KEMA KUR, EAC
Additional information	connected vertically

DIMENSIONS

Length	60.2 mm
Width	6 mm
Height TS 35/7.5	56 mm

CONNECTION DATA

Connections	4
Number of levels	2

Plug gauge acc. EN 60 947-1	A4
Cross connect channels	1
Number of test pick off options	1
Cross section single wire from	0.2 mm ²
Cross section single wire to	4 mm ²
Cross section stranded wire from	0.2 mm ²
Cross section stranded wire to	4 mm ²
Cross section stranded with ferrule from	0.2 mm ²
Cross section stranded with ferrule to	4 mm ²
Rated wire cross section from (AWG)	22
Rated wire cross section to (AWG)	12
Stripping length	9 mm
Screw size	M 3
Screw type	Slotted
Torque min	0.5
Torque max	1

MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

APPROVALS

Rated voltage CSA	300 V
Rated current CSA	30 A
CSA test standard	C22.2 No 158
Rated voltage CSAus	300 V
Rated current CSAus	30 A
CSAus test standard	UL 1059
EAC test standard	TR ZU 004/2011
KEMA KEUR test standard	EN 60947-7-1:2009

ADDITIONAL DATA

Tariff code	85369010
-------------	----------

Country of origin	CZ
Weight	14.1 g
Pack size	100
Type of terminal	Screw Terminals, DIN Rail terminals