

FEED THROUGH TERMINALS - RK 2.5-240MM²

RK

1122.5

RK 95 Blue, 95mm² Feed through terminal, multi-foot

- Screw in cross connectors
- Material polyamide 6.6 - UL94-V2
- Various colour options
- Temperature resistance -40 °C...+105 °C
- Multi-foot TS35/TS32 options



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	95 mm ²
Colour	Blue
Rated voltage IEC	1000 V
Rated current IEC	232 A
Mounting	TS 35 and TS 32
Rated impulse voltage	8 kV
Overvoltage category	III
Contamination degree	3
Approvals	UL, CSA, GL, CSA US, KEMA KUR, EAC
Additional information	with housing pegs and allen screws

DIMENSIONS

Length	84 mm
Width	25 mm
Height TS 35/7.5	88.5 mm
Height TS 32	94 mm

CONNECTION DATA

Connections	2
Number of levels	1
Plug gauge acc. EN 60 947-1	B12
Cross section single wire from	25 mm ²
Cross section single wire to	95 mm ²
Cross section stranded wire from	35 mm ²
Cross section stranded wire to	95 mm ²
Cross section stranded with ferrule from	35 mm ²
Cross section stranded with ferrule to	95 mm ²
Rated wire cross section from (AWG)	2
Rated wire cross section to (AWG)	4/0
Stripping length	30 mm
Screw size	M 8
Screw type	Hexagon/Allen key
Torque min	6
Torque max	12
Banded wire up to	16.6 x 6.0 mm

MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

APPROVALS

Rated voltage UL	600 V
Rated current UL	230 A
UL test standard	UL 1059
Rated voltage CSA	600 V
Rated current CSA	230 A
CSA test standard	C22.2 No 158
Rated voltage CSAus	600 V
Rated current CSAus	230 A
CSAus test standard	UL 1059

GL test standard	IEC 60947-7-1:2002
EAC test standard	TR ZU 004/2011
KEMA KEUR test standard	EN 60947-7-1:2009

ADDITIONAL DATA

Tariff code	85369010
Country of origin	CZ
Weight	189.6 g
Pack size	10
Type of terminal	Screw Terminals, DIN Rail terminals

