


EARTH TERMINALS - ZSL 2.5-16MM²

ZSL, ZSLD

3527.2
ZSL 4/4A GNYE

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	4 mm ²
Colour	Green/yellow
Mounting	TS 35
Overvoltage category	III
Contamination degree	3
Approvals	UL, CSA, GL, CSA US, cUL, KEMA KUR, EAC

DIMENSIONS

Length	93 mm
Width	6.1 mm
Height TS 35/7.5	42 mm

CONNECTION DATA

Connections	4
Number of levels	1
Plug gauge acc. EN 60 947-1	A4
Cross connect channels	0
Number of test pick off options	2
Cross section single wire from	0.5 mm ²
Cross section single wire to	6 mm ²

Cross section stranded wire from	0.6 mm ²
Cross section stranded wire to	6 mm ²
Cross section stranded with ferrule from	0.5 mm ²
Cross section stranded with ferrule to	4 mm ²
Rated wire cross section from (AWG)	20
Rated wire cross section to (AWG)	10
Stripping length	12 mm

MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-40 °C
Operating temperature to	120 °C

APPROVALS

UL test standard	UL 1059
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
cUL test standard	C22.2 No 158
GL test standard	IEC 60947-7-2:2009
EAC test standard	TR ZU 004/2011
KEMA KEUR test standard	EN 60947-7-2:2009

ADDITIONAL DATA

Tariff code	85369010
Country of origin	CZ
Weight	20.8 g
Pack size	100

