


EARTH TERMINALS - ZSL 2.5-16MM²

ZSL, ZSLD

3598.2

ZSL 10/2A GNYE

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	10 mm ²
Colour	Green/yellow
Mounting	TS 35
Overvoltage category	III
Contamination degree	3
Approvals	UL, CSA, CSA US, KEMA KUR, EAC

DIMENSIONS

Length	73.5 mm
Width	10.1 mm
Height TS 35/7.5	50.5 mm

CONNECTION DATA

Connections	2
Number of levels	1
Plug gauge acc. EN 60 947-1	B6
Cross connect channels	0
Number of test pick off options	2
Cross section single wire from	1.5 mm ²
Cross section single wire to	16 mm ²

Cross section stranded wire from	1.5 mm ²
Cross section stranded wire to	10 mm ²
Cross section stranded with ferrule from	1.5 mm ²
Cross section stranded with ferrule to	10 mm ²
Rated wire cross section from (AWG)	16
Rated wire cross section to (AWG)	6
Stripping length	18 mm

MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-40 °C
Operating temperature to	120 °C

APPROVALS

UL test standard	UL 1059
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
EAC test standard	TR ZU 004/2011
KEMA KEUR test standard	EN 60947-7-2:2009

ADDITIONAL DATA

Tariff code	85369010
Country of origin	CZ
Weight	34 g
Pack size	50

