

**COMPACT TERMINALS FOR TS15/TS35
RAIL - ZSRK/ZSL 2.5MM²**

ZSRK, ZSLN

3602.2
ZSLN 2,5/3A GNYE

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0

**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Rated wire cross section	2.5 mm ²
Colour	Green/yellow
Mounting	TS 35
Overvoltage category	III
Contamination degree	3
Approvals	UL, CSA, CSA US, cUL, KEMA KUR, EAC

DIMENSIONS

Length	55 mm
Width	5.1 mm
Height TS 35/7.5	36.5 mm

CONNECTION DATA

Connections	3
Number of levels	1
Plug gauge acc. EN 60 947-1	A3
Cross connect channels	1
Number of test pick off options	2

Cross section single wire from	0.5 mm ²
Cross section single wire to	4 mm ²
Cross section stranded wire from	0.5 mm ²
Cross section stranded wire to	4 mm ²
Cross section stranded with ferrule from	0.5 mm ²
Cross section stranded with ferrule to	2.5 mm ²
Rated wire cross section from (AWG)	20
Rated wire cross section to (AWG)	12
Stripping length	10 mm

MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-40 °C
Operating temperature to	120 °C

APPROVALS

UL test standard	UL 1059
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
cUL test standard	C22.2 No 158
EAC test standard	TR ZU 004/2011
KEMA KEUR test standard	EN 60947-7-2:2009

ADDITIONAL DATA

Tariff code	85369010
Country of origin	CZ
Weight	7.65 g
Pack size	100