


DOUBLE DECK TERMINALS - ZRKD 2.5MM²

ZRKD, ZSLD

3563.5
ZRKD 2,5/SV BU

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	2.5 mm ²
Colour	Blue
Rated voltage IEC	500 V
Rated current IEC	24 A
Mounting	TS 35
Rated impulse voltage	6 kV
Overvoltage category	III
Contamination degree	3
Approvals	UL, CSA, GL, CSA US, KEMA KUR, EAC
Additional information	connected vertically

DIMENSIONS

Length	83.6 mm
Width	5.1 mm
Height TS 35/7.5	53 mm

CONNECTION DATA

Connections	4
-------------	---

Number of levels	2
Plug gauge acc. EN 60 947-1	A3
Cross connect channels	1
Number of test pick off options	4
Cross section single wire from	0.5 mm ²
Cross section single wire to	4 mm ²
Cross section stranded wire from	0.5 mm ²
Cross section stranded wire to	4 mm ²
Cross section stranded with ferrule from	0.5 mm ²
Cross section stranded with ferrule to	2.5 mm ²
Rated wire cross section from (AWG)	20
Rated wire cross section to (AWG)	12
Stripping length	10 mm

MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-40 °C
Operating temperature to	120 °C

APPROVALS

Rated voltage UL	300 V
Rated current UL	10 A
UL test standard	UL 1059
Rated voltage CSA	300 V
Rated current CSA	10 A
CSA test standard	C22.2 No 158
Rated voltage CSAus	300 V
Rated current CSAus	10 A
CSAus test standard	UL 1059
GL test standard	IEC 60947-7-1:2009
EAC test standard	TR ZU 004/2011
KEMA KEUR test standard	EN 60947-7-1:2009

ADDITIONAL DATA

Tariff code	85369010
-------------	----------

Country of origin	CZ
Weight	15.1 g
Pack size	100

