


## TRIPLE DECK TERMINALS - PIKD 2.5MM<sup>2</sup>, PVMAK

PIKD, PVMAK

27047.6

PVMAK 2.5/SV Grey, 2.5mm<sup>2</sup> linked triple deck motor terminal with earth

- Push In technology
- Linked versions
- Colour marked
- Earth versions
- Motor connection terminal



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Rated wire cross section	2.5 mm <sup>2</sup>
Colour	Grey
Rated voltage IEC	800 V
Rated current IEC	20 A
Mounting	Mounting rail TS 35/7.5
Rated impulse voltage	6 kV
Overvoltage category	III
Contamination degree	3

#### DIMENSIONS

Length	99.5 mm
Width	5.1 mm
Height TS 35/7.5	92.6 mm
Height	91.1 mm

#### CONNECTION DATA

Connections	3 x 2 + 1
Number of levels	3
Plug gauge acc. EN 60 947-1	A3
Cross connect channels	3

Cross section single wire from	0.14 mm <sup>2</sup>
Cross section single wire to	4 mm <sup>2</sup>
Cross section stranded wire from	0.14 mm <sup>2</sup>
Cross section stranded wire to	2.5 mm <sup>2</sup>
Cross section stranded with ferrule from	0.14 mm <sup>2</sup>
Cross section stranded with ferrule to	2.5 mm <sup>2</sup>
Rated wire cross section from	26 AWG
Rated wire cross section to	12 AWG
Stripping length	10 mm

### MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-40 °C
Operating temperature to	120 °C

### ADDITIONAL DATA

Tariff code	85369010
Country of origin	CZ
Weight	26.77 g
Pack size	50
Number of terminals per level	2

