


EARTH TERMINALS - SNAP ON - SSL 2.5-35 MM²

Screw Terminal Earth Terminals - SSL

17130.2

SSL 16/2A, Snap on 16mm earth terminal

- Snap on construction
- Secure fixings on both sides of the rail
- Can be cross connected
- Material polyamide 6.6- UL94-V0
- Temperature resistance -40 °C...+120 °C



PRODUCT DESCRIPTION

Snap on Earth terminals that connect on both sides of the rail (up to 35mm) giving a stable connection
50mm version uses a conventional clamp to rail system

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	16 mm ²
Colour	Green/yellow
Mounting	TS 35
Overvoltage category	III
Contamination degree	3
Approvals	UL, CSA, CSA US, KEMA KUR, EAC

DIMENSIONS

Length	53 mm
Width	12.1 mm
Height TS 35/7.5	55 mm

CONNECTION DATA

Connections	2
Number of levels	1
Plug gauge acc. EN 60 947-1	A7

Cross connect channels	1
Number of test pick off options	1
Cross section single wire from	1.5 mm ²
Cross section single wire to	25 mm ²
Cross section stranded wire from	1.5 mm ²
Cross section stranded wire to	25 mm ²
Cross section stranded with ferrule from	1 mm ²
Cross section stranded with ferrule to	16 mm ²
Rated wire cross section from (AWG)	16
Rated wire cross section to (AWG)	4
Stripping length	14 mm
Screw size	M 5
Screw type	Slotted
Torque min	2.5
Torque max	3

MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-40 °C
Operating temperature to	120 °C

APPROVALS

UL test standard	UL 1059
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
EAC test standard	TR ZU 004/2011
KEMA KEUR test standard	EN 60947-7-2:2009

ADDITIONAL DATA

Tariff code	85369010
Country of origin	CZ
Weight	41.65 g
Pack size	50
Type of terminal	Screw Terminals, DIN Rail terminals

