**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# PLUG-IN CONNECTION SYSTEM - ZST

ZRKS, ZSTK

3662.2
ZSLS 2.5/2A/1S , Feed-through, 2 cable, 1 plug, Gree/Yellow



- Wire connection type: tension-spring connection
- Versatile mounting on TS15, TS35 or as free coupling
- Ratings 500 V, 24 A
- Touch-safe construction

### PRODUCT DESCRIPTION

The plug-in connection system ZST is a plug-in system that allows you to achieve a rated current up to 24 A with a rated voltage up to 500 V.

The terminals and the pluggable connectors have a touch-safe design and can be configured easily and combined according to the particular needs of your application.

The basic terminals and connectors can also be coded to make sure the correct plug is mated with the correct socket, when using multiple sets.

All plugs & base terminals have the option of additional snap-on locking latches and strain relief mechanism to ensure that the connected wire and plugs are firmly secured

The ZSTK 2.5 couplings are available as rail-mounted version (for TS15 and TS35) or as a free coupling.

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Rated wire cross section** | 2.5 mm² |

| | |
|---|---|
| **Colour** | Green/yellow |
| **Mounting** | TS 35 |
| **Overvoltage category** | III |
| **Contamination degree** | 3 |
| **Approvals** | UL, CSA, CSA US, cUL, KEMA KUR, EAC |

## DIMENSIONS

| | |
|---|---|
| **Length** | 64 mm |
| **Width** | 5.1 mm |
| **Height TS 35/7.5** | 39.5 mm |
| **Height** | 38.5 mm |

## CONNECTION DATA

| | |
|---|---|
| **Connections** | 3 |
| **Number of levels** | 1 |
| **Plug gauge acc. EN 60 947-1** | A3 |
| **Cross connect channels** | 1 |
| **Number of test pick off options** | 1 |
| **Cross section single wire from** | 0.5 mm² |
| **Cross section single wire to** | 4 mm² |
| **Cross section stranded wire from** | 0.5 mm² |
| **Cross section stranded wire to** | 4 mm² |
| **Cross section stranded with ferrule from** | 0.5 mm² |
| **Cross section stranded with ferrule to** | 2.5 mm² |
| **Rated wire cross section from (AWG)** | 20 |
| **Rated wire cross section to (AWG)** | 12 |
| **Stripping length** | 10 mm |

## MATERIALS

| | |
|---|---|
| **Insulation material** | Polyamide 6.6 |
| **Flammability class** | UL94-V0 |
| **Operating temperature from** | -40 °C |
| **Operating temperature to** | 120 °C |

## APPROVALS

| | |
|---|---|
| **UL test standard** | UL 1059 |

| | |
|---|---|
| **CSA test standard** | C22.2 No 158 |
| **CSAus test standard** | UL 1059 |
| **cUL test standard** | C22.2 No 158 |
| **EAC test standard** | TR ZU 004/2011 |
| **KEMA KEUR test standard** | EN 60947-7-2:2009 |

## ADDITIONAL DATA

| | |
|---|---|
| **Tariff code** | 85369010 |
| **Country of origin** | DE |
| **Weight** | 12 g |
| **Pack size** | 100 |

