


## PLUG-IN CONNECTION SYSTEM - ZST

ZRKS, ZSTK

3665.2

ZSLS 2.5/2S, Feed-through, 2 plug, Green/Yellow

- Wire connection type: tension-spring connection
- Versatile mounting on TS15, TS35 or as free coupling
- Ratings 500 V, 24 A
- Touch-safe construction



### PRODUCT DESCRIPTION

The plug-in connection system ZST is a plug-in system that allows you to achieve a rated current up to 24 A with a rated voltage up to 500 V.

The terminals and the pluggable connectors have a touch-safe design and can be configured easily and combined according to the particular needs of your application.

The basic terminals and connectors can also be coded to make sure the correct plug is mated with the correct socket, when using multiple sets.

All plugs & base terminals have the option of additional snap-on locking latches and strain relief mechanism to ensure that the connected wire and plugs are firmly secured

The ZSTK 2.5 couplings are available as rail-mounted version (for TS15 and TS35) or as a free coupling.

## TECHNICAL DATA

### GENERAL DATA

---

Colour	Green/yellow
Mounting	TS 35
Overvoltage category	III
Contamination degree	3
Approvals	UL, CSA, CSA US, cUL, KEMA KUR, EAC

## DIMENSIONS

Length	54 mm
Width	5.1 mm
Height TS 35/7.5	39.5 mm
Height	38.5 mm

## CONNECTION DATA

Connections	2
Number of levels	1
Cross connect channels	1
Number of test pick off options	0

## MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-40 °C
Operating temperature to	120 °C

## APPROVALS

UL test standard	UL 1059
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
cUL test standard	C22.2 No 158
EAC test standard	TR ZU 004/2011
KEMA KEUR test standard	EN 60947-7-2:2009

## ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	10.97 g
Pack size	100

