


FEED THROUGH TERMINALS - ZRK 2.5-16 MM²

Tension Spring Terminals - ZRK

3597.1

ZRK 10/2A Green, 10mm² Tension spring, feed through

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0
- 2, 3 & 4 connections



PRODUCT DESCRIPTION

The tension spring range of terminals for wire cross-sections from 0.2 mm² to 16 mm² includes: the **ZRK/ZSL** series of feed-through and PE terminals, the double-level **ZRKD/ZSLD**, the **ZIKD** three-level terminal blocks, motor-connection terminals, (blade) disconnect terminals, fused terminals, direct-mount terminals, and initiator/actuator terminals for transmitting positioning, encoder and sensors signals.

Tension spring technology is ideal for high vibration applications and will save up to 50% of the time against a traditional screw terminal.

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	10 mm ²
Colour	Green
Rated voltage IEC	1000 V
Rated current IEC	57 A
Load current max	57 A
Mounting	TS 35
Rated impulse voltage	8 kV
Overvoltage category	III
Contamination degree	3
Approvals	UL, CSA, CSA US, KEMA KUR, EAC

DIMENSIONS

Length	73.5 mm
Width	10.1 mm
Height TS 35/7.5	50.5 mm

CONNECTION DATA

Connections	2
Number of levels	1
Plug gauge acc. EN 60 947-1	B6
Cross connect channels	2
Number of test pick off options	2
Cross section single wire from	1.5 mm ²
Cross section single wire to	16 mm ²
Cross section stranded wire from	1.5 mm ²
Cross section stranded wire to	10 mm ²
Cross section stranded with ferrule from	1.5 mm ²
Cross section stranded with ferrule to	10 mm ²
Rated wire cross section from (AWG)	16
Rated wire cross section to (AWG)	6
Stripping length	18 mm

MATERIALS

Insulation material	Polyamide 6.6
---------------------	---------------

Flammability class	UL94-V0
Operating temperature from	-40 °C
Operating temperature to	120 °C

APPROVALS

Rated voltage UL	500 V
Rated current UL	55 A
UL test standard	UL 1059
Rated voltage CSA	500 V
Rated current CSA	55 A
CSA test standard	C22.2 No 158
Rated voltage CSAus	500 V
Rated current CSAus	55 A
CSAus test standard	UL 1059
EAC test standard	TR ZU 004/2011
KEMA KEUR test standard	EN 60947-7-1:2009

ADDITIONAL DATA

Tariff code	85369010
Country of origin	CZ
Weight	26 g
Pack size	50

