

## N25

Universal input digital meter for measurement of d.c. voltage or d.c. current, temperature from Pt100 sensors and J, K thermocouples, a.c. voltage and a.c. current.

N25T25XX  
5 Digit Panel Meter, Pt100 (400°C) input, 20-40V ac/dc, 24V output



- Universal input (Programmable)
- Wide voltage, AC/DC control
- 5 Digit LED display

## PRODUCT DESCRIPTION

Please refer to the image below for ordering information.

\*\*Part numbers have changed from ending with E0 to M0, please be advised any part numbers below that end in E0 will say M0 in the datasheet. The product is the same.\*\*

TABLE 1. ORDERING CODES:									
	N25	X	X	X	XX	XX	X	X	
Input kind:									
standard: voltage, current		S							
temperature: thermocouples, resistance thermometers		T							
a.c. signals		Z							
d.c. signals: high voltage and high current		H							
Input:									
see table 2		X							
Supply:									
230 V a.c.								1	
110 V a.c.								2	
24 V a.c.								3	
85...253 V a.c./d.c. with supply output 24 V/30 mA*								4	
20...40 V a.c./d.c. with supply output 24 V/30 mA*								5	
Unit:									
see table 3						XX			
Version:									
standard								00	
non-standard settings								NS	
custom-made**								XX	
Language:									
Multilingual (polish-english)									M
other**									X
Acceptance tests:									
without extra requirements									0
with an extra quality inspection certificate									1
acc. to customer's request**									X

  

TABLE 2. INPUT SIGNALS				
Nr	N25S	N25T	N25Z	N25H
1	0...20 mA	Pt100: -50...150°C	100 V a.c.	±100 V d.c.
2	4...20 mA	Pt100: -50...400°C	250 V a.c.	±250 V d.c.
3	0...60 mV	Thermocouple J	400 V a.c.	±400 V d.c.
4	0...10 V	Thermocouple K	1 A a.c.	±1 A d.c.
5	±60 mV		5 A a.c.	±5 A d.c.
6	±10 V		20...500 Hz	0...100 V d.c.
7				0...250 V d.c.

  

TABLE 3. CODES OF PRINTED UNITS:					
Code	Unit	Code	Unit	Code	Unit
00	without unit	06	mA	12	bar
01	°C	07	kA	13	kPa
02	%	08	kV	14	MPa
03	A	09	Hz		
04	V	10	turns	XX	on order
05	mV	11	rpm		

  

TABLE 4. EXAMPLE OF NON-STANDARD SETTINGS:	
Parameter	Range/Value
Decimal point	000,0 for I, U
Averaging time	1 s
Upper measurement overflow	99999
Lower measurement overflow	-19999
Individual characteristic	enabled
Parameter a of the individual characteristic	5
Parameter b of the individual characteristic	0

  

Order example 1 :	Order example 2 :
The code N25Z-2 1 04 00 E 0 means:	The code N25S-1 4 02 E 1 means:
N25Z - digital meter for a.c. signals	N25S - digital meter for d.c. signal
2 - input: 250 V a.c.	1 - input: 0...20mA
1 - supply: 230 V a.c.	4 - supply: 85...253 V a.c.
04 - unit: V	02 - unit: %
00 - standard version	NS - non-standard settings, display range: 0...100.0
M - Multilingual version	M - Multilingual version
0 - without extra requirements	1 - with an extra quality inspection certificate

\* - the output is only in N25S and N25T meters  
\*\* - after agreeing with the manufacturer

## TECHNICAL DATA

Digit height	14 mm
IP class	IP65
Number of digits	5
Supply voltage	20-40V ac/dc

Temperature operational max

55 °C

Temperature operational min

-10 °C



