

## N30H

High voltage DC digital panel meter for measurement of d.c. current and d.c. voltage up to 5 A and 600 V.

### N30H11XX

Panel Meter, 2 x OC Outputs, RS-485, 1A Output 85-253V ac



- DC current and voltage up to 600V
- Wide voltage, AC/DC control
- 5 Digit, 3 colour programmable display

## PRODUCT DESCRIPTION

Please refer to the image below for ordering information.

### Part number key

Digital panel meter	N30H -	X	X	XX	XX	X
<b>Supply voltage:</b>						
85..253 V a.c./d.c.	1					
20..40 V a.c./d.c.	2					
<b>Additional outputs:</b>						
lack	0					
RS-485, analog outputs	1					
RS-485, analog outputs switched-over relay outputs AL3, AL4	2					
<b>Unit:</b>						
code number of the unit acc. table 2				XX		
<b>Kind of execution:</b>						
standard					00	
custom-made					XX	
<b>Acceptance tests:</b>						
without extra additional requirements						8
with an extra quality inspection certificate						7
acc. to customer's agreement						X

## TECHNICAL DATA

<b>Additional functions</b>	<p>Conversion of any measured value into current or voltage analog signal.</p> <p>Storage of minimal and maximal values for all measured quantities. 21-point rescaling for the measured value (does not apply to N30P and N27P).</p> <p>Password protection. Programmable current and voltage transformer ratio (applies to N27P and N30P).</p>
<b>Digital interface</b>	RS-485 Modbus Slave - Option
<b>Dimensions</b>	96 x 48 x 93 mm

<b>Display</b>	Yes
<b>Input type</b>	d.c. current 6 A, d.c. voltage 600 V
<b>IP class</b>	IP65
<b>Mounting</b>	Panel mount
<b>Number of digits</b>	5
<b>Number of rows</b>	1
<b>Outputs</b>	analog, RS485, 2 relays
<b>Supply voltage</b>	85-253V ac/dc
<b>Temperature operational max</b>	55 °C
<b>Weight</b>	0.2 kg

