OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

N30H

High voltage DC digital panel meter for measurement of d.c. current and d.c. voltage up to 5 A and 600 V.

N30H20XX
Panel Meter, 2x OC Outputs, 20-60V dc



- DC current and voltage upto 600V
- Wide voltage, AC/DC control
- 5 Digit, 3 colour programmable display

PRODUCT DESCRIPTION

Please refer to the image below for ordering information.

Part number key

Digital panel meter N30H -	X	X	XX	XX	X
Supply voltage:					
85..253 V a.c./d.c.	1				
20..40 V a.c./d.c.	2				
Additional outputs:					
lack		0			
RS-485, analog outputs		1			
RS-485, analog outputs swiched-over relay outputs AL3, AL4		2			
Unit:					
code number of the unit acc. table 2			XX		
Kind of execution:					
standard				00	
custom-made				XX	
Acceptance tests:					
without extra additional requirements					8
with an extra quality inspection certificate					7
acc. to customer's agreement					X

;

TECHNICAL DATA

Additional functions	Conversion of any measured value into current or voltage analog signal. Storage of minimal and maximal values for all measured quantites. 21-point rescaling for the measured value (does not apply to N30P and N27P). Password protection. Programmable current and voltage transformer ratio (applies to N27P and N30P).
Digital interface	RS-485 Modbus Slave - Option
Dimensions	96 x 48 x 93 mm

Display	Yes
Input type	d.c. current 6 A, d.c. voltage 600 V
IP class	IP65
Mounting	Panel mount
Number of digits	5
Number of rows	1
Outputs	2 relays (NO)
Supply voltage	20-40V ac/dc
Temperature operational max	55 °C
Weight	0.2 kg











