OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

N30O

Pulse/Frequency digital panel meter for measurement of pulses, frequency, rotational speed, period and worktime.

N30O20XX
Panel Meter, 2x OC Outputs, 20-60V dc



- DC Pulse input for frequency or speed
- Wide voltage, AC/DC control
- 5 Digit, 3 colour, Programmable display

PRODUCT DESCRIPTION

Please refer to the image below for ordering information.

Part number key

Digital panel meter N30O -	X	X	XX	XX	X	X
Supply voltage:						
85..253 V a.c./d.c.	1					
20..40 V a.c./d.c.	2					
Additional outputs:						
lack		0				
RS-485, analog outputs		1				
RS-485, analog outputs swiched-over relay outputs AL3, AL4		2				
Unit:						
code number of the unit acc. table 2			XX			
Version:						
standard				00		
custom-made*				XX		
Language:						
Polish					P	
English					E	
Other**					X	
Acceptance tests:						
without extra additional requirements						0
with an extra quality inspection certificate						1

;

TECHNICAL DATA

Additional functions	Conversion of any measured value into current or voltage analog signal. Storage of minimal and maximal values for all measured quantites. 21-point rescaling for the measured value (does not apply to N30P and N27P). Password protection. Programmable current and voltage transformer ratio (applies to N27P and N30P).
Digital interface	RS-485 Modbus Slave - Option
Dimensions	96 x 48 x 93 mm

Display	Yes
Input type	pulses, frequency, rotational speed, period, worktime counter, encoder
IP class	IP65
Mounting	Panel mount
Number of digits	5
Number of rows	1
Outputs	2 relays (NO)
Supply voltage	20-40V ac/dc
Temperature operational max	55 °C
Weight	0.2 kg







